

### Kiln Dried, Planer Regularised, Treated Softwood

<b>Species:</b>	European Redwood ( <i>pinus sylvestris</i> ) & European Whitewood/Spruce ( <i>picea abies</i> )
<b>Treatment:</b>	Preservative treatment to User Class 2 (refer to table below)
<b>Strength Grading:</b>	C16 or C24
<b>Country of Origin:</b>	Latvia & Sweden
<b>Certification:</b>	FSC® Certified
<b>Density:</b>	550 kg/m <sup>3</sup> (+/-10%)

#### Stock Sizes Available (Other Sizes Available On Request):

Nominal Size:	Finish Size (mm):
47mm x 50mm	46mm x 45mm
47mm x 75mm	46mm x 70mm
47mm x 100mm	46mm x 95mm
47mm x 125mm	46mm x 120mm
47mm x 150mm	46mm x 145mm
47mm x 175mm	46mm x 170mm
47mm x 200mm	46mm x 195mm
47mm x 225mm	46mm x 220mm
47mm x 250mm	46mm x 245mm
75mm x 100mm	73mm x 95mm
75mm x 150mm	73mm x 145mm
75mm x 175mm	73mm x 170mm
75mm x 200mm	73mm x 195mm
75mm x 225mm	73mm x 220mm
100mm x 100mm	95mm x 95mm
100mm x 200mm	95mm x 195mm
<b>Lengths Available:</b>	2.4m, 3.0m, 3.6m, 4.2m, 4.8m, 5.4m, 6.0m, 6.6m, 7.2m, 8.4m



Preservative Treatment Use Classes			
Use Class	General Service Conditions	Exposure To Wetting During Service	Example Of Use
<b>1</b>	Above ground, covered and dry	None	Internal - cupboards, mouldings
<b>2</b>	Above ground, covered and risk of wetting	Occasional	Trusses, joists, studs
<b>3</b>	Above ground, not covered	Frequent	Fence rails, decking, cladding
<b>4</b>	In contact with ground or fresh water	Permanent	Fence posts, decking supports in ground contact
<b>5</b>	In salt water	Permanent	Groynes, jetties

**Ascot**  
t: 01344 874 137  
e: ascot@thetimbergroup.co.uk

**Clapham**  
t: 0207 720 9494  
e: clapham@thetimbergroup.co.uk

**High Wycombe**  
t: 01494 521 421  
e: highwycombe@thetimbergroup.co.uk

**Hoddesdon**  
t: 01992 460 000  
e: hoddesdon@thetimbergroup.co.uk

**Maidstone**  
t: 01622 738 246  
e: maidstone@thetimbergroup.co.uk

**Poole**  
t: 01202 735 735  
e: poole@thetimbergroup.co.uk