

QPly FSC® Certified Chinese Plywood

QPly is a top quality panel that is suitable for use in 'exterior' conditions as defined in EN636:2012+A1:2015			
Service Class:	EN636-3S	Glue Bond:	EN314-2 Class 3
Where indicated by * in the thickness table below the glue bond has been independently tested in the UK and the samples met the requirements of EN314-2 Class 3. For other thicknesses refer to the declaration of performance.			
All plywood used externally should be both edge-sealed and treated with a suitable wood preservative			
Formaldehyde Class:	E1	Environmental Claim:	FSC® 100% Certified
Face and Back Veneer Species:	Eucalyptus*, Beech^		
Face and Back Veneer Species Country of Origin:	Uruguay*, Germany^		
Core Veneer Species:	Eucalyptus, Whiteteak		
Core Veneer Species Origin:	Solomon Islands		
The species claimed to be present in QPly have been independently verified in the UK by microscopic analysis			
The supply chain of FSC® 100% QPly has been assessed for compliance with the European Timber Regulation as 'Negligible Risk'			

Length	Width	Thickness	Pack Size
2440mm	1220mm	9mm	100 sheets
2440mm	1220mm	12mm	75 sheets
2440mm	1220mm	15mm	60 sheets
2440mm	1220mm	18mm	50 sheets

Ascot
t: 01344 874 137
e: ascot@thetimbergroup.co.uk

Clapham
t: 0207 720 9494
e: clapham@thetimbergroup.co.uk

High Wycombe
t: 01494 521 421
e: highwycombe@thetimbergroup.co.uk

Hoddesdon
t: 01992 460 000
e: hoddesdon@thetimbergroup.co.uk

Maidstone
t: 01622 738 246
e: maidstone@thetimbergroup.co.uk

Poole
t: 01202 735 735
e: poole@thetimbergroup.co.uk